




80A, 75V N-CHANNEL POWER MOSFET

DESCRIPTION

The UTC **UTT80N75** is an N-Channel power MOSFET, it uses UTC's advanced technology to provide customers with a minimum on-state resistance, low gate charge and high switching speed.

FEATURES

- * 80A, 75V, $R_{DS(ON)}=10m\Omega$ @ $V_{GS}=10V$, $I_D=20A$
- * Low gate charge (typical 117nC)
- * High switching speed



ORDERING INFORMATION

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
UTT80N75L-TA3-T	UTT80N75G-TA3-T	TO-220	G	D	S	Tube

Note: Pin Assignment: G: Gate D: Drain S: Source

UTT80N75L-TA3-T	(1)Packing Type	(1) T: Tube
	(2)Package Type	(2) TA3: TO-220
	(3)Lead Free	(3) L: Lead Free, G: Halogen Free

■ **ABSOLUTE MAXIMUM RATINGS** ($T_A=25^{\circ}\text{C}$)

PARAMETER		SYMBOL	RATINGS	UNIT
Drain-Source Voltage		V_{DSS}	75	V
Gate-Source Voltage		V_{GSS}	± 25	V
Drain Current	Continuous	I_{D}	80	A
	Pulsed	I_{DM}	320	A
Avalanche Energy	Single Pulsed	E_{AS}	330	mJ
Power Dissipation		P_{D}	167	W
Junction Temperature		T_{J}	$-50 \sim +150$	$^{\circ}\text{C}$
Storage Temperature Range		T_{STG}	$-50 \sim +150$	$^{\circ}\text{C}$

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ **THERMAL CHARACTERISTICS**

PARAMETER		SYMBOL	RATINGS	UNIT
Junction to Ambient		θ_{JA}	62.5	$^{\circ}\text{C/W}$
Junction to Case		θ_{JC}	0.75	$^{\circ}\text{C/W}$

■ **ELECTRICAL CHARACTERISTICS**

PARAMETER		SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
OFF CHARACTERISTICS							
Drain-Source Breakdown Voltage		BV _{DSS}	I _D =250μA, V _{GS} =0V	75			V
Drain-Source Leakage Current		I _{DSS}	V _{DS} =75V, V _{GS} =0V			10	μA
Gate-Source Leakage Current	Forward	I _{GSS}	V _{GS} =+25V, V _{DS} =0V			+100	nA
	Reverse		V _{GS} =-25V, V _{DS} =0V			-100	nA
ON CHARACTERISTICS							
Gate Threshold Voltage		V _{GS(TH)}	V _{DS} =V _{GS} , I _D =250μA	2		4	V
Static Drain-Source On-State Resistance		R _{DS(ON)}	V _{GS} =10V, I _D =20A		10	12	mΩ
DYNAMIC PARAMETERS							
Input Capacitance		C _{ISS}	V _{GS} =0V, V _{DS} =25V, f=1.0MHz		3700		pF
Output Capacitance		C _{OSS}			730		pF
Reverse Transfer Capacitance		C _{RSS}			240		pF
SWITCHING PARAMETERS							
Total Gate Charge		Q _G	V _{GS} =10V, V _{DD} =60V, I _D =40A, I _G =3.33mA		117		nC
Gate to Source Charge		Q _{GS}			27		nC
Gate to Drain Charge		Q _{GD}			47		nC
Turn-ON Delay Time		t _{D(ON)}	V _{DD} =30V, I _D =1.0A, R _G =4.6Ω, V _{GS} =10V		25		ns
Rise Time		t _R			25		ns
Turn-OFF Delay Time		t _{D(OFF)}			66		ns
Fall-Time		t _F			30		ns
SOURCE- DRAIN DIODE RATINGS AND CHARACTERISTICS							
Maximum Body-Diode Continuous Current		I _S		80			A
Maximum Body-Diode Pulsed Current		I _{SM}		320			A
Drain-Source Diode Forward Voltage		V _{SD}	I _S =80A, V _{GS} =0V			1.5	V
Body Diode Reverse Recovery Time		t _{RR}					ns

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.